

Specifications

		SC-6	SC-8	SC-12	SC-16	SC-22	SC-28	SC-36	SC-42	SC-50
Carrier weight	t	0.7 - 1.2	1 - 1.7	1.2 - 2.2	1.5 - 3.7	2.2 - 5.3	3 - 7.5	4.0 - 10.0	4.0 - 12.0	7.0 - 12.0
Weight with top bracket and tool	kg	65	90	110	150	225	275	365	445	498
Diameter of the tool	mm	37	45	47	55	65	72	76	84	94
Working length of the tool	mm	270	279	289	335	370	400	400	439	425
Input power*	kW	4	6	7	10	13	15	21	25	27
Frequency	blows/ min	1150	1600	1700	1500	1310	1420	1550	1450	1137
Total length with tool, without top bracket	mm	865	897	926	1036	1182	1263	1379	1499	1550
Oil flow	l/min	12 - 23	15 - 30	17 - 35	25 - 50	30 - 65	40 - 75	55 - 100	70 - 120	75 - 125
Working pressure of the breaker	bar	110	120	120	120	120	120	125	125	130
Acceptable back-pressure	bar	20	35	32	32	30	30	20	20	20
Clip Bucket		-	•	•	•	•	•	-	-	-
Clip Ram		-	•	•	•	•	•	-	-	-

* Possible increase of the breaker's power by 50% thanks to the energy recovery system.

